

# Lifetime warranty on electronics (2-years on lamps). (3-Year warranty on CP-24V14 electronics)

• 2-Year long-life lamps.

#### DUCT MOUNT UNIT SPECIFICATIONS

DM18003 Size (L x W x D) 10.75" x 4.25" x 2.75" 16" Germicidal H lamp penetrates duct 15.5" 12" Germicidal H lamp penetrates duct 12.25" Auto-sensing multivoltage ballast 120 - 240 VAC 50/60 HZ. 50 WATT .40/.20 AMP

### **REMOTE UNIT SPECIFICATIONS**

#### CP-RM18003

Power supply dimensions: Size (L x W x D) 6h x 5.75w x 1.75 d Auto-sensing multivoltage ballast 120 - 240 VAC 50/60 HZ. 50 WATT .40/.20 AMP

Remote Lamp Socket Dimensions: Size (L x W) 3.5" x 2.75" 16" Germicidal H lamps penetrates duct 15.5"

12" Germicidal H lamps penetrates duct 12.25"

MUV7-50OU size (L x W x D) 4" x 4" x 3.75" Odor control chamber penetrates duct 4.5"

### ECONOMY REMOTE UNIT SPECIFICATIONS

CP-24V14 size (L x W x D) 16.25" x 2.5" x 2.5" 14" Germicidal lamp penetrates duct 13.25" 24 V ballast 24 VAC 50/60 HZ. 20-watts,

### LAMP SPECIFICATIONS

#### DM18003 and CP-RM18003 units

5" UVV Lamp Output at 184 nanometers Rated life Lamp dimensions Quartz diameter 16" Twin-Tube Germicidal H Lamp 12" Twin-Tube Germicidal H Lamp Rated life Lamp dimensions Glass diameter

#### CP-24V14

14" Germicidal Lamp Intensity at 1 meter Rated life Lamp dimensions Glass diameter 8 watts, 425 mA 50 mg per hour maximum 2 years 5" from base to end 15 mm (T5) 36 watts, 425 mA 180 µW/cm2 24 watts, 425 mA 140 µW/cm2 2 years 13" or 16.5" from base to end 30 mm (15 mm x 2)

20 watts, 425 mA 55 μW/cm2 2 years 14" from base to end 15 mm

### UV GERMICIDAL AIR PURIFIER SPEC SHEET



## DM18003

MULTIVOLTAGE UV GERMICIDAL AIR PURIFIER WITH ACTIVATED OXYGEN

\* Patented Ozone Chamber provides precise control of ozone output that can be easily adjusted by the homeowner.

- Powerful germicidal twin-tube H lamp outputs up to three times more microwatts than a single-tube lamp.
- 140 Microwatts (12" lamps).
- 180 Microwatts (16" lamps).
- For duct mounting or duct-board mounting with our optional duct-board mount plate.

**CP-RM18003** 

• ETL certified.



IFETIME

DUAL REMOTE MULTIVOLTAGE UV GERMICIDAL AIR PURIFIER WITH ACTIVATED OXYGEN

\* Patented Ozone Chamber provides precise control of ozone output that can be easily adjusted by the homeowner.

- Powerful germicidal twin-tube H lamp outputs up to three times more microwatts than a single-tube lamp.
- Patented odor-control chamber easily adjusted by the homeowner.
- Moisture-proof lamp connector and mid-cord connector.
- Remote units it in tight spaces.
- 140 Microwatts (12" lamps).
- 180 Microwatts (16" lamps).
- ETL certified.

### CP-24V14



24 VOLT REMOTE UV GERMICIDAL LAMP UVC germicidal lamp for irradiating surfaces.

\_\_\_\_ 55 Microwatt 14" lamp.

- Remote units fit in tight spaces.
- Perfect for surface irradiation.
- Easy mounting with our heavy duty magnetic Z bracket that has an 80# pull force magnet that also converts to a duct mount plate.
- Moisture-proof lamp connector and mid-cord connector.
- LED system monitor indicates power on. A second LED monitors the lamp operation.